


	Standard	Result
Size		1219,2 X 177,8 mm
Thickness		3,0 mm
Wear layer		0,55 mm
Surface treatment		Kguard+ PU coating
Guarantee	Light industrial	10 year
	Commercial	12 year
	Domestic	15 year
Bevelled edge		No
Standards	EN 649	Heterogeneous PVC
Classification	EN 685- Light industrial	42: Light industrial general
	EN 685- Commercial	33: Commercial heavy
	EN 685- Domestic	23: Domestic heavy
Reaction to fire	EN 13501-1	B _{f1} -s1
	EN ISO 9239-1	Pass
	EN ISO 11925-2	Pass
Staining resistance	EN 423	Class 0
Light fastness	EN ISO 105-B02	≥7
Abrasion resistance	EN 660-2	Group T
Dimensional stability	EN 434	≤ 0.25%
Acoustic Impact noise reduction	EN ISO 717-2 / EN ISO 140-8	ΔL _w = 4 db
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433	≤ 0.1mm
Castor chair continuous use	EN 425	Pass
Mass per unit area	EN430	5044 g/m ²
Thermal conductivity	ISO 8302	0,0147 m ² K/W
Slip resistance	DIN 51130	R10
	DIN 51097	Class B
	EN 13893	DS
VOC emission	NF EN ISO 1600	A+ (<250µg/m ²)
Adhesive	Universal	Yes
	Acrylic	Yes
	Epoxy	Yes
	High Temperature	Yes
	Pressure sensitive	Yes
Recycling		Suitable



For more information:
 T: +44 (0)1386 820105
 F: +44 (0)1386 820132
info@designflooring.com